

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
3 October 2002 (03.10.2002)

PCT

(10) International Publication Number
WO 02/078123 A1

(51) International Patent Classification⁷: **H01Q 1/24**

(21) International Application Number: **PCT/SE02/00532**

(22) International Filing Date: **20 March 2002 (20.03.2002)**

(25) Filing Language: **English**

(26) Publication Language: **English**

(30) Priority Data:
0101067-7 23 March 2001 (23.03.2001) SE
60/286,412 25 April 2001 (25.04.2001) US
0102183-1 20 June 2001 (20.06.2001) SE

(71) Applicant (for all designated States except US): **TELEFONAKTIEBOLAGET L M ERICSSON (publ)**
[SE/SE]; S-126 25 Stockholm (SE).

(72) Inventors; and


(75) Inventors/Applicants (for US only): **BOLIN, Thomas** [SE/SE]; Drätselgränd 7, S-226 47 Lund (SE). **YING, Zhinong** [CN/CN]; Skyttelinjen 50, S-226 49 Lund (SE). **ANDERSSON, Johan** [SE/SE]; Hillerödsvägen 12 D, S-217 47 Malmö (SE). **DA SILVA FRAZAO, André** [SE/SE]; Amiralsgatan 72, S-214 37 Malmö (SE). **NOR-DENSTRÖM, Peter** [SE/SE]; Johanna Tvätterskas gränd 7, S-239 35 Skanör (SE).

(74) Agents: **STRÖM, Tore et al.**; Ström & Gulliksson IPC AB, P.O. Box 4188, S-203 13 Malmö (SE).

(81) Designated States (national): AE, AG, AL, AM, AT, AU (utility model), AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, CZ (utility model), DE, DE (utility model), DK, DK (utility model), DM, DZ, EC, EE, EE (utility model), ES, FI, FI (utility model), GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR,

[Continued on next page]

(54) Title: **A BUILT-IN, MULTI BAND, MULTI ANTENNA SYSTEM**



(57) Abstract: A build-in, multi band, multi antenna system (1) for a portable communication device (10) has a first antenna (2, 4, 5), which is resonant in first and second frequency band. A second antenna (3) is resonant in a fourth frequency band. The first antenna, the parasitic element and the second antenna are provided on a common flexible substrate.

WO 02/078123 A1



KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SD, SE, SG, SI, SK, SK (utility model), SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZM, ZW.

(BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

(84) **Designated States (regional):** ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

A BUILT-IN, MULTI BAND, MULTI ANTENNA SYSTEM

Technical Field

5 The present invention relates to mobile telephones and similar types of portable communication devices that need several commercial frequency bands to communicate on. More specifically, the invention relates to a built-in, multi band, multi antenna system for such mobile tele-
10 phones, etc.

Background Art

A basic problem of today is to be able to put one or several very small antennas on e.g. a mobile telephone.
15 Main emphasis is put on size, but a good electrical performance is also important. Now when Bluetooth™ applications have become a world standard, an additional frequency band must be covered in future mobile telephones. It is very hard to include this in an already existing antenna, most
20 commonly a built-in antenna. Another way is to include a new antenna to handle Bluetooth™ communication. Usually the available space is very small - in fact, too small in reality. The antennas will often have to be located very close to each other, since generally, the best position is
25 at the top of the telephone.

This kind of complicated internal antenna system needs a very sophisticated mechanical process, involving for example MID, metal painting and printed film. The designer must be very careful to get good isolation between
30 the main antenna and the Bluetooth™ antenna.

State of the art today is one single antenna, usually a built-in patch antenna with one grounding and one feeding pin, functioning at two commercial frequency bands: GSM and DCS or maybe GSM and PCS. No Bluetooth™ antenna has been
35 observed on the market together with such an antenna in a mobile telephone.

Thus, the known antennas are only dual band, and a Bluetooth™ antenna is not included.

Summary of the Invention

5 It is an object of the present invention to propose a very compact multi band, multi antenna system, with a cheap and sophisticated mechanical concept to get good isolation by clever design of a parasitic element as a high impedance block.

10 The object of the invention is achieved by an antenna system according to the attached independent patent claim.

Other objects, features and advantages of the present invention will appear from the following detailed
15 disclosure of a preferred embodiment, from the enclosed drawings as well as from the subclaims.

Brief Description of the Drawings

A presently preferred exemplifying embodiment of an
20 antenna system according to the present invention will now be described in more detail with reference to the accompanying drawings, where:

FIG 1 is a schematic perspective view of the antenna system,

25 FIG 2 is schematic side view of the antenna system shown in FIG 1,

FIG 3 is a schematic perspective view of a mobile telephone with an antenna carrier and an antenna connector for the antenna system of FIGs 1 and 2,

30 FIG 4 corresponds to FIG 3, with the addition of the antenna system of FIGs 1 and 2 in an unfolded condition,

FIG 5 shows the unfolded antenna system of FIG 4 together with the antenna connector mounted on a printed circuit board,

FIG 6 is a return loss diagram for a main antenna and a Bluetooth™ antenna, which are comprised in the antenna system,

FIG 7 illustrates the isolation between the two
5 antennas of FIG 6,

FIG 8 is a dimensioned drawing of the presently preferred embodiment of the antenna system, and

FIG 9-12 are alternative embodiments of the antenna system according to the invention.

10

Detailed Disclosure

A simplified illustration of the antenna system 1 according to the invention is given in FIGs 1 and 2. The antenna system has a main antenna 2 for GSM/DCS/PCS and a
15 separate smaller Bluetooth™ antenna 3 positioned very close to the main antenna 2. As seen in FIG 2, the antennas have a folded distribution which occupies a first plane where most of the antenna pattern is located, a second plane which is perpendicular to the first plane, and a
20 third plane which is perpendicular to the second plane and parallel to the first plane.

The main antenna 2 is a built-in patch with parasitic element, whereas the smaller Bluetooth™ antenna 3 is a PIFA, however folded a little bit to fit the small space
25 available. The combination of the antennas, their individual positions, and the folding together with the electrical connection are noteworthy features.

A significant advantage with the antenna system according to the present invention is the size reduction
30 that obtained by placing the antennas close together as well as the folding of the antenna patterns.

The main antenna 2 comprises a dual band PIFA antenna with a GSM part 4 and a DCS part 5. In addition, the main antenna 2 comprises a parasitic PCS part 6. The main an-
35 tenna 2 and the Bluetooth™ PIFA antenna 3 are printed on

the same flexible substrate (not shown in the drawings) and constitute a common flex film.

The metal trace of the parasitic PCS part 6 is located between the main antenna 2 and the Bluetooth™ antenna 3. It is resonant at PCS 1900 MHz, about $\frac{1}{4}$ wavelength, and will function as a high impedance blocking between the main antenna 2 and the Bluetooth™ antenna 3.

By arranging the antennas in this manner, it is possible to reduce the overall size of the antenna system compared to if the parasitic element was not present. As can be understood, moving the antennas further apart, which would be necessary in the absence of the parasitic element, would increase the isolation between the main antenna and the Bluetooth™ antenna.

The antenna system 1 has five connection traces 7a-7e, which all are located in the third plane. Of these connection traces, the main antenna 2 has a ground trace 7a ("Ground #1") and a feed trace 7b ("Feed #1") for the GSM part 4 and the DCS part 5. The parasitic PCS part 6 has only a ground trace 7c ("Ground #2"), whereas the Bluetooth™ antenna 3 has a ground trace 7d ("Ground #3") as well as a feed trace 7e ("Feed #2"), as shown in FIG 1. The actual width of the feed traces is a tradeoff between size and performance. By widening the feed traces, a better performance would be achieved. However, wider feed traces result in an increased size of the antenna system.

As seen in FIG 2, the antenna system 1 is connected to radio circuitry on a printed circuit board 13 (FIG 5) through electrical feeding 8. As appears from FIGs 3-5, the electrical feeding 8 is implemented as an antenna connector 11, which is mounted to the printed circuit board 13 and comprises a group of five pogo pins 12 (one for each connection trace 7a-7e).

In a preferred embodiment, the flex film with the antenna system 1 is placed on a plastic antenna carrier 9,

which will keep the film at its correct position with respect to the printed circuit board 13. FIG 3 illustrates the antenna carrier 9 together with the antenna connector 11 and the primary side of a mobile telephone 10.

5 The material used for the antenna carrier will affect the antenna performance. This is due to that the antenna carrier will act as a dielectric loading, changing the resonance frequencies of the antennas slightly. A lossy material, i.e. a material with a large dielectric constant,
10 will give a better VSWR (Voltage Standing Wave Ratio) and hence a broader bandwidth, but will at the same time provide a lower antenna gain. As mentioned above, in the preferred embodiment the antenna carrier is made of plastic. However, other materials such as ceramic, mica, or
15 glass could also be used as carrier material, depending on the desired working characteristics of the antenna system.

FIG 4 illustrates the base of the antenna system 1 unfolded in one plane above the antenna carrier 9. The antenna connector 11 with its pogo pins 12 is shown
20 underneath the antenna carrier 9.

FIG 5 illustrates, again, the antenna system 1 unfolded above the antenna connector 11 and the pogo pins 12. The naked printed circuit board 13 is also shown.

FIG 6 shows return loss for the main antenna 2 and
25 the Bluetooth™ antenna 3. As seen, the antennas are tuned (designed) to work at slightly too high frequencies. This is done in order to compensate for losses that are introduced by the plastic cover and the rest of the mechanics underneath.

30 FIG 7 illustrates the isolation between the two antennas of FIG 6. Obviously, the isolation is very good, even in the highest band despite the short distance between the antennas.

FIG 8 is a dimensioned drawing of the presently
35 preferred embodiment of the antenna system.

Finally, FIGs 9-12 illustrates four alternative embodiments of the antenna system according to the invention. As can be seen from the figures different parts of the antenna system may look different depending on e.g.
5 the amount of space available inside the portable communication device.

The invention has been described above with reference to a presently preferred embodiment example. However, other embodiments than the one described above as well as many
10 modifications, variations and equivalent arrangements are possible within the scope of the invention, as defined by the appended independent patent claim.

CLAIMS

1. A built-in, multi band, multi antenna system (1) for a portable communication device (10), comprising, in combination:
- a first antenna (2, 4, 5), which is resonant in first and second frequency bands,
 - a parasitic element (6), which is positioned adjacent to the first antenna and is resonant in a third frequency band, and
 - a second antenna (3), which is resonant in a fourth frequency band,
- wherein the first antenna, the parasitic element and the second antenna are provided on a common flexible substrate.
2. An antenna system as in claim 1, wherein the first antenna (2, 4, 5) and the second antenna (3) are PIFA antennas.
3. An antenna system as in claim 2, wherein the first antenna (2, 4, 5) has a first feed trace (7b) and a first ground trace (7a), the parasitic element (6) has a second ground trace (7c), and the second antenna (3) has a second feed trace (7e) and a third ground trace (7d).
4. An antenna system as in claim 3, wherein the first antenna (2, 4, 5) has a GSM part (4) and a DCS part (5), the parasitic element (6) is operative in the PCS band, and the second antenna (3) is a Bluetooth™ antenna.

5. An antenna system as in any preceding claim, wherein the parasitic element (6) is located between the first antenna (2, 4, 5) and the second antenna (3) so as to provide high impedance blocking between the antennas.

5

6. An antenna system as in any preceding claim, further comprising an antenna carrier (9), upon which said common flexible substrate is provided in a folded distribution.

10

7. A portable communication device (10) having a printed circuit board (13), **characterized by** an antenna system (1) according to any of claims 1-6, and

15

an antenna connector (11) for connecting the antenna system to the printed circuit board (13).

8. A portable communication device as in claim 7, the antenna system (1) being defined by claim 3, wherein the antenna connector (11) comprises a group of five pogo pins (12), each of which is aligned with a respective one of said first feed trace (7b), said first ground trace (7a), said second ground trace (7c), said second feed trace (7e) and said third ground trace (7d).

25

9. A portable communication device as in claim 7 or 8, wherein the device is a mobile telephone.

1/10




Fig 1

2/10




Fig 2

3/10




Fig 3

4/10





Fig 4

5/10

*Fig 5*

6/10

Return loss for main and Bluetooth antenna




Fig 6

7/10

Isolation between the antennas





Fig 7

8/10



PET thickness 75 μm $\pm 10\%$
 Cu thickness 20 μm $\pm 5\%$
 Adhesive thickness 40 μm $\pm 10\%$
 Total thickness 135 μm $\pm 9\%$
 Plating on contact point:
 1-4 μm Ni, min 0,5 μm Au
 Flex is to be put on ... (material TBD)

All dimensions according to 3D-file:
 13042-kre10595
 General tolerances:
 Cu pattern $\pm 0,05$
 PET pattern 0-15mm: $\pm 0,05$
 >15mm: $\pm 0,10$
 From PET edge to Cu pattern: $\pm 0,15$

Fig 8

9/10




Fig 9




Fig 10

10/10



Fig 11




Fig 12

INTERNATIONAL SEARCH REPORT

International Application No

PCT/SE 02/00532

A. CLASSIFICATION OF SUBJECT MATTER
IPC 7 H01Q1/24

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 H01Q

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the International search (name of data base and, where practical, search terms used)

PAJ, INSPEC, EPO-Internal

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	WO 01 17063 A (ERICSSON TELEFON AB L M) 8 March 2001 (2001-03-08) page 11, line 27 - line 28 page 12, line 1 - line 5 page 13, line 8 - line 26 figures 5-10 ---	1-9
A	EP 0 892 459 A (NOKIA MOBILE PHONES LTD) 20 January 1999 (1999-01-20) column 5, line 56 - line 58 column 6, line 1 column 6, line 12 - line 27 column 8, line 30 - line 58 column 9, line 1 - line 27 figures 7-11 --- -/--	1-9

☒ Further documents are listed in the continuation of box C.☒ Patent family members are listed in annex.

* Special categories of cited documents :

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the international search

24 June 2002

Date of mailing of the international search report

12.07.2002

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Christian Rasch

INTERNATIONAL SEARCH REPORT

International Application No
PCT/SE 02/00532

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT		
Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	ALI M ET AL: "Analysis of integrated inverted-F antennas for bluetooth applications." IEEE CONFERENCE ON ANTENNAS AND PROPAGATION FOR WIRELESS COMMUNICATION, IEEE-APS 2000, WALTHAM, MA. (USA), 6 - 8 November 2000, pages 21-24, XP002902522 the whole document ---	1-4
A	ROWELL C R ET AL: "A COMPACT PIFA SUITABLE FOR DUAL-FREQUENCY 900/1800-MHZ OPERATION" IEEE TRANSACTIONS ON ANTENNAS AND PROPAGATION, IEEE INC. NEW YORK, US, vol. 46, no. 4, 1 April 1998 (1998-04-01), pages 596-598, XP000750738 ISSN: 0018-926X see section "Dual-frequency antenna design" figure 3 ---	1-6
A	PATENT ABSTRACTS OF JAPAN vol. 1995, no. 08, 29 September 1995 (1995-09-29) & JP 07 131234 A (NIPPON MEKTRON LTD), 19 May 1995 (1995-05-19) abstract -----	1-9

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/SE 02/00532

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
WO 0117063	A	08-03-2001	US 6408190 B1	18-06-2002
			AU 6572800 A	26-03-2001
			WO 0117063 A1	08-03-2001
			EP 1212808 A1	12-06-2002

EP 0892459	A	20-01-1999	FI 972897 A	09-01-1999
			EP 0892459 A1	20-01-1999
			FI 981571 A	09-01-1999
			US 6140966 A	31-10-2000

JP 07131234	A	19-05-1995	NONE	
